



ATEX TRACKED UNDERCARRIAGES

Gerotto's tracked undercarriages have been designed for creating customized miniexcavators, adaptable to most different environments. All Gerotto undercarriages can go up slopes of up to 30% and reach a speed of 5 km/h on level surfaces.

Gerotto's tracked undercarriages are made of stainless steel, to guarantee a better resistance to wear and chemical agents.

Gerotto can provide, on request, undercarriages with ATEX certification for Zone 2, Zone 1 or Zone 0 to work in potentially explosive environments. It is also possible to obtain the equivalent international certification (IECEx), or the specific one for North America (FM Approved in accordance with regulatory norm NFPA70/NEC500), China (CNEx) and Australia (ANZEx).



WEIGHT AND DIMENSIONS				
	Weight	Height	Length	Width
XXS	60 [Kg] 132 [lb]	200 [mm] 8"	730 [mm] 29"	390 [mm] 15"
XS	130 [Kg] 287 [lb]	280 [mm] 11"	970 [mm] 38"	420 [mm] 16,5"
S	145 [Kg] 320 [lb]	280 [mm] 11"	970 [mm] 38"	420 [mm] 16,5"
M	150 [Kg] 331 [lb]	300 [mm] 12"	985 [mm] 39"	500 [mm] 20"
L	170 [Kg] 375 [lb]	300 [mm] 12"	1170 [mm] 46"	500 [mm] 20"
XL	235 [Kg] 518 [lb]	360 [mm] 14"	1225 [mm] 48"	530 [mm] 21"