



essenza

# EF-XF-FS

emission friendly- extra formula- fuel saving  
series



*power from within*

# EF LINE



4x4/SUV



CAR

**essenza sintetica EF** is a line of emission friendly motor oils that are intended for use as catalyst compatible oils in vehicles with DPF and TWC in high performance car and light van diesel and gasoline engines. These oils are formulated with synthetic base oils and superior viscosity modifiers to meet low friction, low viscosity and shear stability characteristics that allow the oil to maintain its viscosity grade during use and achieve fuel efficiency. The use of low to medium SAPS additive technology increases the after-treatment devices life and maintains the vehicles fuel economy. These oils are unsuitable for use in some engines therefore please consult the vehicle manufacturer manual before use.



200L



20L



1L/4L



1L/4L

## Available SAE grades and specifications

0W-30, 5W-30, 5W-40

ACEA C4, C3, C2, API SN/CF, MB 229.51, MB 229.31, MB-Approval 226.51, Renault RN0720, RN0710, RN0700, VW504.00/507.00, BMW LL-04, GM DEXOS 2, PORSHE A40

# FS AND XF LINE



4x4/SUV



CAR

**essenza sintetica FS and XF** are a range of extended oil drain interval motor oils specifically designed to meet the requirements set by european OEM and ACEA (European Car Manufacturers Association) in gasoline engines, car & light van diesel engine vehicles not fitted with after treatment devices. The FS oils are specifically intended for use in engines designed to use low friction-low viscosity oils with a high-temperature, high-shear properties to reduce friction and hence achieve specific fuel economy targets. The XF oils are specifically designed for high performance engines operating under severe service conditions also when direct diesel injection technology is used. Some low friction oils might be unsuitable for use in some engines. Consult manufacturer manual or handbook before use.



200L



20L



1L/4L



1L/4L

## Available SAE grades and specifications

0W-40, 5W-30, 5W-40, 10W-40, 15W-40

ACEA A1/B1, ACEA A3/B4, A5/B5, , API SL/SM/SN/CF, Renault RN0700/RN0710, Jaguar Land Rover STJLR.03.5003 FORD M2C 913-B, 913 C & 913 D, BMW LL-01, VW 502.00, 505.00, 50101, MB 229.1, MB 229.3, MB 229.5, Opel GM LL-A-025/B-025, Porsche A40, PSA B71 2300 B71 2296

The information and packshots contained herein is provided as a guideline and may change without notice. Italcro, therefore declines any liability for the improper use of the product information. We suggest that you contact our technicians in order to obtain up-to-date information on product specifications and applications.

for more information, visit us at  
[www.essenzalubricants.it](http://www.essenzalubricants.it)